

Model	Filter Area (Sq. Ft.)	Flow Rate (15 gpm/sq.ft)	Filter Turnover Rates (Hours)		Total Media (Pounds)	Sand/Gravel (Pounds)
			6 Hours	8 Hours		
THS3484	19.0	285	102,600	136,800	1950	1350/600
THS4272	19.7	295	106,200	141,600	2600	2100/500
THS4284	23.2	348	125,280	167,040	3000	2400/600
THS4296	26.7	400	144,000	192,000	3500	2800/700

NSF-approved for 5-20 gpm/sq. ft.

Product No.	DESCRIPTION
143484	THS 34 in. x 84 in.
144272	THS 42 in. x 72 in.
144284	THS 42 in. x 84 in.
144296	THS 42 in. x 96 in.

Product No.	OPTIONAL KITS
155700	THS Single Tank Manifold Kit w/Butterfly valves
155720	THS Dual Tank Manifold Kit w/Butterfly valves
155701	THS Single Tank 6 in. FP Kit w/Diaphragm valves
155721	THS Dual 34 in. dia. 6 in. FP Kit w/Diaphragm valves
155730	THS Dual 42 in. dia. 6 in. FP Kit w/Diaphragm valves
155800	WA-KIT Wedge Anchor Kit (1)
155850	BVA-KIT 1/2 in. Ball Valve Adapter Kit for manual air relief (1)
156150	Flowmeter Saddle Kit
156100	Temperature Probe Kit

1. One each required per tank purchased.

Product No.	CONTROLLERS^
156850	Single THS Autobackwash controller
156800	Dual THS Autobackwash controller
156400	Single THS Semi-automatic controller 6 in. FP
156450	Dual THS Semi-automatic controller 6 in. FP

^Must be used with Diaphragm Valves

